# FIRE TECHNOLOGY SERVICES

# **CONFIDENTIAL REPORT**

Ref:

30/03347

Page 2 of 2

Client:

TECH and Just FX Limited

Sample:

Just FX - FETTI and STREAMER tissue, referenced:

JFX-07/001

Performance Standard:

BS 5867: Part 2: 1980 (1993)

Type B performance requirements

**Test Method:** 

BS 5438: 1976 Test 2

Flame application time = 15s

**Cleansing Pretreatment:** 

None (tested in the "as received" condition)

## **Summary of Results:**

"The results may not apply to situations where there is restricted air supply or prolonged exposure to large sources of intense heat as in a conflagration."

Specimen	11	2↓	31	4→	5←	6→
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris	No	No	No	No	No	No
Duration of flaming, s	0	0.49	0	0	0	0
Duration of afterglow, s	0	0	0	0	0	0
Vertical hole size, mm	108	110	161	115	128	123
Horizontal hole size, mm	25	27	26	26	26	30

#### **Assessment:**

### BS 5867: Part 2: 1980 (1993) Type B performance requirements

No part of any hole nor any part of the lowest boundary of any flame shall reach the upper edge or either vertical edge of any specimen and there shall be no separation of any flaming debris from any specimen.

Tested in the "as received	" condition this Just FX	- FETTI and STREAME	R tissue complies with the
Type B performance requi	rements of BS 5867: Pa	art 2: 1980 (1993).	

------ END OF REPORT ------

Reported by: D R Young (Laboratory Technician)

Countersigned by: P M Eaton (Operational Head)



